






# LIGHTNING ELIMINATORS

WWW.LIGHTNINGPROTECTION.COM

## Product Offering

### Selection Guide

	FG300K	FG225K	FGB200	TLX130K	TLX50K
					
Surge Capacity Per Phase	300,000 amps	225,000 amps	200,000 amps	132,000 amps	50,000 amps
Modes Protected	L-N, L-L, N-G, L-G	L-N, L-L, N-G, L-G	L-N, L-L, N-G, L-G	L-N, L-L, N-G, L-G	L-N, L-L, N-G, L-G
Failure Indication	LEDs	LEDs	LEDs	LEDs	LEDs
Temperature Limits	-40°F + 185°F (-40°C + 85°C)	-40°F + 185°F (-40°C + 85°C)	-40°F + 185°F (-40°C + 85°C)	-40°F + 185°F (-40°C + 85°C)	-40°F + 185°F (-40°C + 85°C)
Relative Humidity Range	0 – 95% non-condensing	0 – 95% non-condensing	0 – 95% non-condensing	0 – 95% non-condensing	0 – 95% non-condensing
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Housing Enclosure Material	Steel	Steel	Steel	Plastic	Aluminum Cast
NEMA	NEMA 4	NEMA 4	NEMA 4/ Polycarbonate	NEMA 4X	NEMA 6
UL 1449 5 <sup>th</sup> Ed. Listed	*Yes	*Yes	*Yes	*Yes	*Yes
Warranty	10 Years	10 Years	10 Years	10 Years	10 Years
Code Compliance	UL Type 1 Listed SPD	UL Type 1 Listed SPD	UL Type 1 Listed SPD	UL Type 1 Listed SPD	UL Type 1 Listed SPD
Shipping Dimensions	24" x 20" x 12"	18" x 18" x 10"	10" x 10" x 10"	10" x 10" x 10"	8" x 6" x 4"
Weight	24 Lbs	30 Lbs	10 Lbs	4 Lbs	3 Lbs